



R5 SERIES
1 1/2" FLUID PATH

SERIES R5 FEATURES
FOR 1" THROUGH 1 1/2" I.D. HOSE

UNIQUE STANDARD HOSE REEL CAPACITY	R5000 SERIES REEL DIMENSIONS												APPROX. WEIGHT		MODEL	HOSE CAPACITY				I. D.		
	inches mm												lb	kg		feet m						
	Frame Length	Drum Length	Drum Diameter	Frame Width	Head Diameter	Bevel Gear	Electric	Hydraulic	Pneumatic Air (4AM)	Pneumatic Air (4AM)	Overall Height	Center to Base	BEVEL CRANK REWIND See Note # 2 for add on weight option values		SERIES	Head Dia.	Drum LG.	Drum Dia.	1"	1 1/4"	1 3/8"	1 1/2"
	A	B	C	D	E	F	F	F	F	FE	G	H	NET	SHIP					25 mm	32 mm	35 mm	38 mm
	22	16	11 1/4	21	19	26	27 3/4	27 3/4	25 1/2	22 5/8	22 1/2	13	92	122	R5200 - 19 - 16 x 11				55	45	45	40
	559	406	286	533	483	660	705	705	648	575	572	330	202	268				180	148	148	131	
	26	20	11 1/4	21	19	30	32 3/4	31 3/4	29 1/2	22 5/8	22 1/2	13	95	125	R5200 - 19 - 20 x 11				70	65	60	55
	660	508	286	533	483	762	832	806	749	575	572	330	209	275				230	213	197	180	
	18	12	11 1/4	21	23	22	24 3/4	23 3/4	21 1/2	23 5/8	24 1/2	13	89	119	R5200 - 23 - 12 x 11				95	60	55	50
	457	305	286	533	584	559	629	603	546	600	622	330	196	262				312	197	180	164	
	24	18	11 1/4	21	23	28	30 3/4	29 3/4	27 1/2	23 5/8	24 1/2	13	95	125	R5200 - 23 - 18 x 11				155	90	90	80
	610	457	286	533	584	711	781	756	699	600	622	330	209	275				508	295	295	262	
	26	20	11 1/4	21	23	30	32 3/4	31 3/4	29 1/2	23 5/8	24 1/2	13	97	127	R5200 - 23 - 20 x 11				165	105	100	95
	660	508	286	533	584	762	832	806	749	600	622	330	213	279				541	344	328	312	
	31	25	11 1/4	21	23	35	37 3/4	36 3/4	34 1/2	23 5/8	24 1/2	13	102	132	R5200 - 23 - 25 x 11				220	120	110	105
	787	635	286	533	584	889	959	933	876	600	622	330	224	290				722	394	361	344	
	34	28	11 1/4	21	23	38	40 3/4	39 3/4	37 1/2	23 5/8	24 1/2	13	105	135	R5200 - 23 - 28 x 11				240	145	140	135
	864	711	286	533	584	965	1035	1010	953	600	622	330	231	297				787	476	459	443	
	42	36	11 1/4	21	23	46	48 3/4	47 3/4	45 1/2	23 5/8	24 1/2	13	113	143	R5200 - 23 - 36 x 11				320	190	180	175
	1067	914	286	533	584	1168	1238	1213	1156		622	330	249	315				1050	623	590	574	
	18	12	11 1/4	21	25	22	24 3/4	23 3/4	21 1/2	N / A	26 1/2	14	91	121	R5200 - 25 - 12 x 11				95	85	55	50
	457	305	286	533	635	559	629	603	546		673	356	200	266				312	279	180	164	
	26	20	11 1/4	21	25	30	32 3/4	31 3/4	29 1/2	N / A	26 1/2	14	99	129	R5200 - 25 - 20 x 11				165	155	100	95
	660	508	286	533	635	762	832	806	749		673	356	218	284				541	508	328	312	
	18	12	11 1/4	21	31	22	24 3/4	23 3/4	21 1/2	N / A	32 1/2	17	94	124	R5200 - 31 - 12 x 11				210	155	115	105
	457	305	286	533	787	559	629	603	546		826	432	207	273				689	508	377	344	
	22	16	11 1/4	21	31	26	28 3/4	27 3/4	25 1/2	N / A	32 1/2	17	98	128	R5200 - 31 - 16 x 11				305	205	155	150
	559	406	286	533	787	660	730	705	648		826	432	216	282				1000	672	508	492	
	26	20	11 1/4	21	31	30	32 3/4	31 3/4	29 1/2	N / A	32 1/2	17	102	132	R5200 - 31 - 20 x 11				365	275	200	190
	660	508	286	533	787	762	832	806	749		826	432	224	290				1197	902	656	623	

UNIQUE STANDARD HOSE REEL CAPACITY